



www.agreto.com

AGRETO Weighing Beams

Applications:

- Weighing beams for mounting under cattle squeeze or treatment shoots
- For the construction of weighing platforms
- For indoor and outdoor use, in stables and damp environments

Technical details beams:

- 2 sturdy weighing beams, easy to install
- Available in galvanized or stainless steel
- Length 600, 800 or 1000 mm
- Load cells 4x1000 kg/2200 lb, accuracy +/- 0.02 %
- Total capacity when mounted under a self-supporting platform: 4000 kg/8800 lb (2000/kg/4400 lb per beam)
- Adjustable feet, total height between 85 and 100 mm
- Holes in the feet for mounting on the floor
- Dust- and waterproof according to IP68
- 4 m treadable and UV resistant signal cable from weighing beams to display, waterproof plugs

Technical details display device:

- Dust- and waterproof, made of stainless steel
- 6-digit backlit LCD display, 25 mm high digits
- Resolution 0.5 kg/lb, Zero stabilisation, animal mode, summing function, auto-zero or manual zero
- Power supply 220 VAC, Battery operation by 2x1.5 V

Benefits:

- Robust weighing technology for flexible use
- Stable feet with M16 screws, makes it suitable for the weighing of large livestock
- Easy to mount, also under wooden platforms
- All parts are completely dust- and waterproof, no problems with dampness in outdoor areas or stables
- Internal weighing technology, no problems with dirt
- High weighing accuracy







